



**SAFETY DATA SHEET**  
KWIKGRIP FLOORING GRIPPER & TRIM ADHESIVE

Page 1  
Issued: 15/9/08  
Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** KWIKGRIP FLOORING GRIPPER & TRIM ADHESIVE  
**Product code:** KGGRIP3  
**Company name:** EVERBUILD BUILDING PRODUCTS LTD  
SITE 41, KNOWSTHORPE WAY  
CROSS GREEN INDUSTRIAL ESTATE  
LEEDS  
WEST YORKSHIRE  
LS9OSW  
ENGLAND  
Tel: 0044 113 240 3456  
Fax: 0044 113 240 0024  
Emergency tel: 0044 113 240 3456 (office hours only)  
Email: pault@everbuild.co.uk

**2. HAZARDS IDENTIFICATION**

**Main hazards:** Highly flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.  
**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** ETHYL METHYL KETONE 10-30%  
EINECS: 201-159-0 CAS: 78-93-3  
[F] R11; [Xi] R36; [-] R66; [-] R67

- NAPHTHA (PETROLEUM) HYDROTREATED LIGHT 1-10%  
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67
- NAPHTHA (PETROLEUM) HYDROTREATED HEAVY 1-10%  
CAS: 64742-48-9  
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67
- CYCLOHEXANE 1-10%  
EINECS: 203-806-2 CAS: 110-82-7  
[F] R11; [Xi] R38; [Xn] R65; [-] R67; [N] R50/53

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be mild irritation at the site of contact.  
**Eye contact:** There may be irritation and redness.  
**Ingestion:** There may be irritation of the throat.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

[cont...]

**SAFETY DATA SHEET**

KWIKGRIP FLOORING GRIPPER &amp; TRIM ADHESIVE

**4. FIRST AID MEASURES (ACTION)**

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

- Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.
- Exposure hazards:** Highly flammable. In combustion emits toxic fumes. May form flammable / explosive dust-air mixture.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions:** Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition.
- Environmental precautions:** Do not discharge into drains or rivers.
- Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**7. HANDLING AND STORAGE**

- Handling requirements:** Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.
- Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Hazardous ingredients:** ETHYL METHYL KETONE  
WEL (8 hr TWA): 600 mg/m<sup>3</sup> WEL (15 min STEL): 899 mg/m<sup>3</sup>
- CYCLOHEXANE  
WEL (8 hr TWA): 350 mg/m<sup>3</sup> WEL (15 min STEL): 1050 mg/m<sup>3</sup>
- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

- Hand protection:** Protective gloves.  
**Eye protection:** Safety glasses. Ensure eye bath is to hand.  
**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- State:** Paste  
**Colour:** Beige  
**Odour:** Pungent  
**Evaporation rate:** Fast  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Insoluble  
**Also soluble in:** Most organic solvents.  
**Viscosity:** Highly viscous  
**Boiling point/range°C:** 64  
**Flash point°C:** -10  
**Relative density:** 1.20  
**VOC g/l:** 30%

**10. STABILITY AND REACTIVITY**

- Stability:** Stable under normal conditions. Stable at room temperature.  
**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.  
**Materials to avoid:** Strong oxidising agents. Strong acids.  
**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

- Hazardous ingredients:** CYCLOHEXANE  
ORL MUS LD50 813 mg/kg  
ORL RAT LD50 12705 mg/kg  
**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability:** No data available.  
**Bioaccumulative potential:** No data available.  
**Other adverse effects:** Toxic to aquatic organisms.

**13. DISPOSAL CONSIDERATIONS**

- Disposal operations:** Dispose of according to local or national legislation  
**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SAFETY DATA SHEET**

KWIKGRIP FLOORING GRIPPER &amp; TRIM ADHESIVE

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 1133	<b>ADR Class:</b> 3
<b>Packing group:</b> II	<b>Classification code:</b> F1
<b>Shipping name:</b> ADHESIVES	
<b>Labelling:</b> 3	<b>Hazard ID no:</b> 33

**IMDG / IMO**

<b>UN no:</b> 1133	<b>Class:</b> 3
<b>Packing group:</b> II	<b>EmS:</b> F-E,S-D
<b>Marine pollutant:</b> .	
<b>Labelling:</b> 3	

**IATA / ICAO**

<b>UN no:</b> 1133	<b>Class:</b> 3
<b>Packing group:</b> II	
<b>Packing instructions:</b> 305(P&CA); 307(CAO)	
<b>Labelling:</b> 3	

**15. REGULATORY INFORMATION**

**Hazard symbols:** Highly flammable.  
Dangerous for the environment.



**Risk phrases:** R11: Highly flammable.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.  
S29: Do not empty into drains.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.  
S51: Use only in well-ventilated areas.  
S46: If swallowed, seek medical advice immediately and show this container or label.

**SAFETY DATA SHEET**  
KWIKGRIP FLOORING GRIPPER & TRIM ADHESIVE

NAPTHA (PETROLEUM) HYDROTREATED LIGHT; NAPTHA (PETROLEUM)  
HYDROTREATED HEAVY; CYCLOHEXANE

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.3:** R11: Highly flammable.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.  
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.