



**SAFETY DATA SHEET**  
STICK 2 EXTRA TIME CONTACT ADHESIVE

Page 1  
Issued: 12/05/2010  
Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING**

**Product name:** STICK 2 EXTRA TIME CONTACT ADHESIVE  
**Company name:** EVERBUILD BUILDING PRODUCTS LTD  
SITE 41, KNOWSTHORPE WAY  
CROSS GREEN INDUSTRIAL ESTATE  
LEEDS  
WEST YORKSHIRE  
LS9OSW  
ENGLAND  
Tel: 0044 113 240 3456  
Fax: 0044 113 240 0024  
Emergency tel: 0044 113 240 3456 (office hours only)  
Email: [pault@everbuild.co.uk](mailto:pault@everbuild.co.uk)

**2. HAZARDS IDENTIFICATION**

**Classification under CHIP:** Highly flammable. Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Workplace exposure limit:** This substance does not have a workplace exposure limit.

**PBT:** This substance is not identified as a PBT substance.

**Directive 1999/45/EC:** This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** NAPHTHA (PETROLEUM) HYDROTREATED HEAVY 10-30%

- ACETONE 10-30%  
EINECS: 200-662-2 CAS: 67-64-1  
[F] R11; [Xi] R36; [-] R66; [-] R67  
CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336
- ETHYL METHYL KETONE 10-30%  
EINECS: 201-159-0 CAS: 78-93-3  
[F] R11; [Xi] R36; [-] R66; [-] R67  
CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336
- ETHYL ACETATE 10-30%  
EINECS: 205-500-4 CAS: 141-78-6  
[F] R11; [Xi] R36; [-] R66; [-] R67  
CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336

[cont...]

**SAFETY DATA SHEET**  
STICK 2 EXTRA TIME CONTACT ADHESIVE

- FORMALDEHYDE <1%  
EINECS: 200-001-8 CAS: 50-00-0  
[T] R23/24/25; [C] R34; [Xn] R40; [Sens.] R43  
CLP Class: Carc. 2: H351; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; Skin Corr. 1B: H314; Skin Sens. 1: H317
- PARATERTIARYBUTYLPHENOL <1%  
[Xi] R36/37/38; [N] R51/53; [Sens.] R43

#### 4. FIRST AID MEASURES

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water Jet
- Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

#### 7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

[cont...]

**SAFETY DATA SHEET**  
STICK 2 EXTRA TIME CONTACT ADHESIVE

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25`C. Storage outside these paramaters will dramatically reduce shelf life and invalidates all product warrenties.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Hazardous ingredients:** ACETONE  
UK - 8 hour TWA: 1210 mg/m3  
UK - 15 min. STEL: 3620 mg/m3
- ETHYL METHYL KETONE  
UK - 8 hour TWA: 600 mg/m3  
UK - 15 min. STEL: 899 mg/m3
  - ETHYL ACETATE  
UK - 8 hour TWA: 200 ppm  
UK - 15 min. STEL: 400 ppm
  - FORMALDEHYDE...100%  
UK - 8 hour TWA: 2.5 mg/m3  
UK - 15 min. STEL: 2.5 mg/m3

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- State:** Liquid  
**Colour:** Yellow-orange  
**Odour:** Aromatic  
**Evaporation rate:** Fast  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Insoluble  
**Also soluble in:** Most organic solvents.  
**Viscosity:** Viscous  
**Viscosity test method:** mPa.s

**SAFETY DATA SHEET**  
STICK 2 EXTRA TIME CONTACT ADHESIVE

**Boiling point/range°C:** 110  
**Melting point/range°C:** N/D  
**Flammability limits %: lower:** 1 vol%  
**Flash point°C:** -5  
**Part.coeff. n-octanol/water:** N/D  
**Autoflammability°C:** >200` C  
**Vapour pressure:** <250hPa @20` C  
**Relative density:** ~0.86  
**pH:** N/A

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions. Stable at room temperature.  
**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.  
**Materials to avoid:** Strong oxidising agents. Strong acids.  
**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Acute effects:** Irritating to eyes and skin. May cause lung damage if swallowed.  
**Sensitisation:** May cause sensitisation by skin contact.

**11. TOXICOLOGICAL INFORMATION (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.  
**Persistence and degradability:** No data available.  
**Bioaccumulative potential:** No data available.  
**Other adverse effects:** Toxic to aquatic organisms.  
**PBT identification:** This substance is not identified as a PBT substance.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Dispose of according to local or national legislation  
**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SAFETY DATA SHEET**  
 STICK 2 EXTRA TIME CONTACT ADHESIVE

**14. TRANSPORT INFORMATION**

**ADR / RID**

<b>UN no:</b> 1133	<b>ADR Class:</b> 3
<b>Packing group:</b> III	<b>Classification code:</b> F1
<b>Shipping name:</b> ADHESIVES	
<b>Labelling:</b> 3+EHS	<b>Hazard ID no:</b> 33



**IMDG / IMO**

<b>UN no:</b> 1133	<b>Class:</b> 3
<b>Packing group:</b> III	<b>EmS:</b> 3-05
<b>Marine pollutant:</b> NO	<b>Labelling:</b> 3+EHS

**IATA / ICAO**

<b>UN no:</b> 1133	<b>Class:</b> 3
<b>Packing group:</b> III	<b>Packing instructions:</b> 309(P&CA); 310(PAO)
<b>Labelling:</b> 3+EHS	

**15. REGULATORY INFORMATION (CHIP)**

**Hazard symbols:** Highly flammable.  
 Dangerous for the environment.  
 Harmful.



**Risk phrases:** R11: Highly flammable.  
 R36/38: Irritating to eyes and skin.  
 R43: May cause sensitisation by skin contact.  
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R65: Harmful: may cause lung damage if swallowed.  
 R66: Repeated exposure may cause skin dryness or cracking.  
 R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.  
 S9: Keep container in a well-ventilated place.

**SAFETY DATA SHEET**  
STICK 2 EXTRA TIME CONTACT ADHESIVE

S16: Keep away from sources of ignition - No smoking.

S24: Avoid contact with skin.

S29: Do not empty into drains.

S37: Wear suitable gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Haz. ingredients (label):** ACETONE; ETHYL METHYL KETONE; ETHYL ACETATE; FORMALDEHYDE...100%; NAPHTHA (PETROLEUM) HYDROTREATED HEAVY

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**15. REGULATORY INFORMATION (CLP)**

**16. OTHER INFORMATION**

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.  
\* indicates text in the SDS which has changed since the last revision.

**Risk phrases used in s.3:** R11: Highly flammable.  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.  
R67: Vapours may cause drowsiness and dizziness.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.  
R34: Causes burns.  
R40: Limited evidence of a carcinogenic effect.  
R43: May cause sensitisation by skin contact.  
R36/37/38: Irritating to eyes, respiratory system and skin.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.