



SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED

Page 1

Issued: 28/11/2008

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED
Product code: CON125/250/750
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ACETONE 10-30%
EINECS: 200-662-2 CAS: 67-64-1
[F] R11; [Xi] R36; [-] R66; [-] R67

- CYCLOHEXANE 10-30%
EINECS: 203-806-2 CAS: 110-82-7
[F] R11; [Xi] R38; [Xn] R65; [-] R67; [N] R50/53
- ETHYL ACETATE 10-30%
EINECS: 205-500-4 CAS: 141-78-6
[F] R11; [Xi] R36; [-] R66; [-] R67
- MIXED ALIPHATIC HYDROCARBON 30-50%
[F] R11; [Xi] R38; [N] R51/53; [-] R67

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water Jet

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Hazardous ingredients:** ACETONEWEL (8 hr TWA): 1210 mg/m³ WEL (15 min STEL): 3620 mg/m³

- CYCLOHEXANE

WEL (8 hr TWA): 350 mg/m³ WEL (15 min STEL): 1050 mg/m³

- ETHYL ACETATE

WEL (8 hr TWA): 200 ppm WEL (15 min STEL): 400 ppm

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor**Hand protection:** Impermeable gloves.**Eye protection:** Safety glasses. Ensure eye bath is to hand.**Skin protection:** Impermeable protective clothing.**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Liquid**Colour:** Pale yellow**Odour:** Aromatic**Evaporation rate:** Fast**Oxidising:** Non-oxidising (by EC criteria)**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Boiling point/range°C:** 56**Flammability limits %: lower:** 0.6 vol%**upper:** 11.5 vol%**Flash point°C:** -35**Part.coeff. n-octanol/water:** N/D**Autoflammability°C:** 200°C**Relative density:** 0.82**pH:** N/A**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.

SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** ACETONE
 IVN RAT LD50 5500 mg/kg
 ORL MUS LD50 3 gm/kg
 ORL RAT LD50 5800 mg/kg
- CYCLOHEXANE
 ORL MUS LD50 813 mg/kg
 ORL RAT LD50 12705 mg/kg
 - ETHYL ACETATE
 ORL MUS LD50 4100 mg/kg
 ORL RAT LD50 5620 mg/kg
 SCU RAT LDLO 5 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1133	ADR Class: 3
Packing group: II	Classification code: F1
Shipping name: ADHESIVES	
Labelling: 3	Hazard ID no: 33

**IMDG / IMO**

UN no: 1133	Class: 3
Packing group: II	EmS: F-E,S-D

SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED

Marine pollutant: .**Labelling:** 3**IATA / ICAO****UN no:** 1133**Class:** 3**Packing group:** II**Packing instructions:** 305(P&CA); 307(CAO)**Labelling:** 3**15. REGULATORY INFORMATION****Hazard symbols:** Highly flammable.

Irritant.

Dangerous for the environment.

**Risk phrases:** R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S46: If swallowed, seek medical advice immediately and show this container or label.

Haz. ingredients (label): ACETONE; CYCLOHEXANE; ETHYL ACETATE; MIXED ALIPHATIC HYDROCARBON**Water hazard class:** 2

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION**Risk phrases used in s.3:** R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

STICK 2 ALL PURPOSE CONTACT ADHESIVE - MID SIZED

R67: Vapours may cause drowsiness and dizziness.

R38: Irritating to skin.

R65: Harmful: may cause lung damage if swallowed.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.