



SAFETY DATA SHEET

STICK 2 CONTACT ADHESIVE THINNERS AND CLEANER

Page 1

Issued: 1/11/10

Revision No: 4

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name: STICK 2 CONTACT ADHESIVE THINNERS AND CLEANER
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP: Highly flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Classification under CLP: Aquatic Chronic 2. Toxic to aquatic life with long lasting effects. Eye Irrit. 2. Causes serious eye irritation. Flam. Liq. 3. Flammable liquid and vapour. Skin Irrit. 2. Causes skin irritation. STOT SE 3. May cause drowsiness or dizziness.

Workplace exposure limit: This product has a workplace exposure limit: (UK: WEL 8 hr exposure 191 mg/m3).

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ACETONE 30-50%
EINECS: 200-662-2 CAS: 67-64-1
[F] R11; [Xi] R36; [-] R66; [-] R67
CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336

- MIXED ALIPHATIC HYDROCARBON 30-50%
- ETHYL METHYL KETONE 10-30%
EINECS: 201-159-0 CAS: 78-93-3
[F] R11; [Xi] R36; [-] R66; [-] R67
CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336

[cont...]

4. FIRST AID MEASURES

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
- Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Workplace exposure limits:** UK - 8 hour TWA: 191 mg/m³
UK - 15 min. STEL: 574 mg/m³
- Hazardous ingredients:** ACETONE
UK - 8 hour TWA: 1210 mg/m³
UK - 15 min. STEL: 3620 mg/m³
- ETHYL METHYL KETONE
UK - 8 hour TWA: 600 mg/m³
UK - 15 min. STEL: 899 mg/m³
- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.
- Hand protection:** Impermeable gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Colourless
- Odour:** Aromatic
- Evaporation rate:** Moderate
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Insoluble
- Also soluble in:** Most organic solvents.
- Viscosity:** Non-viscous
- Boiling point/range°C:** 56
- Flammability limits %: lower:** 0.6
upper: 13
- Flash point°C:** -30
- Autoflammability°C:** 200
- Vapour pressure:** 22mm@20`C
- Relative density:** 0.74
- pH:** not app.

10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions. Stable at room temperature.
- Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.
- Materials to avoid:** Strong oxidising agents. Strong acids.
- Haz. decomp. products:** In combustion emits toxic fumes.

SAFETY DATA SHEET

STICK 2 CONTACT ADHESIVE THINNERS AND CLEANER

11. TOXICOLOGICAL INFORMATION**Acute effects:** Irritating to eyes and skin.**11. TOXICOLOGICAL INFORMATION (SYMPTOMS)****Skin contact:** There may be irritation and redness at the site of contact.**Eye contact:** There may be irritation and redness. The eyes may water profusely.**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**PBT identification:** This substance is not identified as a PBT substance.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Dispose of according to local or national legislation**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 3295**ADR Class:** 3**Packing group:** II**Classification code:** F1**Shipping name:** HYDROCARBONS, LIQUID, N.O.S.**Labelling:** 3+EHS**Hazard ID no:** 33**IMDG / IMO****UN no:** 3295**Class:** 3**Packing group:** II**EmS:** F-E,S-D**Marine pollutant:** .**Labelling:** 3+EHS**IATA / ICAO****UN no:** 3295**Class:** 3**Packing group:** II**Packing instructions:** 305(P&CA); 307(CAO)**Labelling:** 3+EHS

[cont...]

15. REGULATORY INFORMATION (CHIP)

Hazard symbols: Highly flammable.
Irritant.
Dangerous for the environment.



Risk phrases: R11: Highly flammable.
R36/38: Irritating to eyes and skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S29: Do not empty into drains.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Haz. ingredients (label): ACETONE; MIXED ALIPHATIC HYDROCARBON; ETHYL METHYL KETONE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

15. REGULATORY INFORMATION (CLP)

Hazard statements: H226: Flammable liquid and vapour.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental



Precautionary statements: P243: Take precautionary measures against static discharge.
P261: Avoid breathing.
P264: Wash thoroughly after handling.

SAFETY DATA SHEET

STICK 2 CONTACT ADHESIVE THINNERS AND CLEANER

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P332+313: If skin irritation occurs: Get medical.

P337+313: If eye irritation persists: Get medical.

P362: Take off contaminated clothing and wash before reuse.

P370+378: In case of fire: Use for extinction.

P391: Collect spillage.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P403+235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of to.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.