



SAFETY DATA SHEET
STICK 2 EPOXY PUTTY - RESIN

Page 1
Issued: 10/11/2008
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: STICK 2 EPOXY PUTTY - RESIN
Product code: S2EPOXPUTTY
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} 50-70%
EINECS: 500-033-5 CAS: 25068-38-6
[Xi] R36/38; [Sens.] R43; [N] R51/53

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Do not induce vomiting. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.
Exposure hazards: In combustion emits toxic fumes.
Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a suitable container.

7. HANDLING AND STORAGE

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Non required

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: White

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: >150

Flash point°C: >150

Relative density: 1.3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents. Amines.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL MUS LD50 15600 mg/kg

ORL RAT LD50 11400 mg/kg

SKN RBT LD50 >20 ml/kg

Chronic toxicity: May cause sensitisation by skin contact.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Non-volatile.

Persistence and degradability: Not biodegradable.

SAFETY DATA SHEET
STICK 2 EPOXY PUTTY - RESIN

Bioaccumulative potential: No data available.
Other adverse effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 3082	ADR Class: 9
Packing group: III	Classification code: M6
Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
Labelling: 9	Hazard ID no: 90



IMDG / IMO

UN no: 3082	Class: 9
Packing group: III	EmS: F-A,S-F
Marine pollutant: .	
Labelling: 9	

IATA / ICAO

UN no: 3082	Class: 9
Packing group: III	
Packing instructions: 914	
Labelling: 9	

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.
 Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.
 R43: May cause sensitisation by skin contact.
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY DATA SHEET
STICK 2 EPOXY PUTTY - RESIN

Safety phrases: S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S46: If swallowed, seek medical advice immediately and show this container or label.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Haz. ingredients (label): BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.