



SAFETY DATA SHEET
STICK 2 TEXTILE ADHESIVE

Page 1
Issued: 10/11/08
Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: STICK 2 TEXTILE ADHESIVE
Product code: S2TEXTADH
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.
Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHANOL 10-30%
EINECS: 200-578-6 CAS: 64-17-5
[F] R11
• ACETONE 10-30%
EINECS: 200-662-2 CAS: 67-64-1
[F] R11; [Xi] R36; [-] R66; [-] R67

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Irritation or pain may occur at the site of contact. Absorption through the skin may occur causing symptoms similar to those of inhalation.
Eye contact: There may be pain and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. Headaches or general malaise may result. There may be vomiting.
Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion. There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

[cont...]

SAFETY DATA SHEET
STICK 2 TEXTILE ADHESIVE

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air. Avoid direct contact with the substance. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ETHANOL
WEL (8 hr TWA): 1920 mg/m³

- ACETONE
WEL (8 hr TWA): 1210 mg/m³ WEL (15 min STEL): 3620 mg/m³

Engineering measures: Ensure lighting and electrical equipment are not a source of ignition. Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). and must be worn if vapour concentration exceeds OES

Hand protection: Impermeable gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Liquid
Colour:	Colourless
Odour:	Sweet-smelling
Evaporation rate:	Fast
Solubility in water:	Insoluble
Viscosity:	Viscous
Boiling point/range°C:	78-120
Flammability limits %: lower:	3.3
upper:	19
Flash point°C:	18
Relative density:	0.8-1
pH:	N/A
VOC g/l:	50% w/w

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions. Stable at room temperature.
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	ETHANOL
	IVN RAT LD50 1440 mg/kg
	ORL MUS LD50 3450 mg/kg
	ORL RAT LD50 7060 mg/kg
	• ACETONE
	IVN RAT LD50 5500 mg/kg
	ORL MUS LD50 3 gm/kg
	ORL RAT LD50 5800 mg/kg
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility:	Readily absorbed into soil.
Persistence and degradability:	Biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no:	1993	ADR Class:	3
Packing group:	II	Classification code:	F1
Shipping name:	FLAMMABLE LIQUID, N.O.S.		
Labelling:	3	Hazard ID no:	33

**IMDG / IMO**

UN no:	1993	Class:	3
Packing group:	II	EmS:	F-E,S-E*
Marine pollutant:	.		
Labelling:	3		

IATA / ICAO

UN no:	1993	Class:	3
Packing group:	II		
Packing instructions:	305(P&CA); 307(CAO)		
Labelling:	3		

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.
Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S46: If swallowed, seek medical advice immediately and show this container or label.

SAFETY DATA SHEET
STICK 2 TEXTILE ADHESIVE

S16: Keep away from sources of ignition - No smoking.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S29: Do not empty into drains.

Haz. ingredients (label): ACETONE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.