

# SAFETY DATA SHEET

EPOXY PRIMER - HARDENER COMPONENT

Page 1

Issued: 15/05/2003

Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** EPOXY PRIMER - HARDENER COMPONENT

**Product code:** EPOXGPPRI5

**Use / description of product:** Sensitising. Irritant.

**Company name:** Everbuild Building Products Ltd

Site 41, Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire

LS9 OSW

England

Tel: 0044 113 240 3456

Fax: 0044 113 200 9418

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** CYCLOALIPHATIC AMINE B >90%  
[Xn] R21/22; [C] R34; [Sens.] R43; [N] R50/53

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Harmful in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

**Inhalation:** Consult a doctor.

[cont...]

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Yellow


**Odour:** Characteristic odour

**Evaporation rate:** Moderate

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Boiling point/range°C:** >200

**Flash point°C:** 220**Relative density:** 1.02**pH:** alkaline**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Chronic toxicity:** May cause sensitisation by skin contact.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** No data available.**Bioaccumulative potential:** No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 3082**ADR Class:** 9**Packing group:** III**Classification code:** M6**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.**Labelling:** 9**Hazard ID no:** 90**IMDG / IMO****UN no:** 3082**Class:** 9**Packing group:** III**EmS:** -**Marine pollutant:** .**Labelling:** 9**IATA / ICAO****UN no:** 3082**Class:** 9**Packing group:** III**Packing instructions:** 914

Labelling: 9

**15. REGULATORY INFORMATION****Hazard symbols:** Corrosive.

Dangerous for the environment.

**Risk phrases:** R21/22: Harmful in contact with skin and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S1/2: Keep locked up and out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S29: Do not empty into drains.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Contains epoxy constituents. See information supplied by the manufacturer.**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Risk phrases used in s.2:** R21/22: Harmful in contact with skin and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.