



SAFETY DATA SHEET
EPOXYSET 112 - HARDENER COMPONENT

Page 1
Issued: 20/11/08
Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPOXYSET 112 - HARDENER COMPONENT
Product code: EPOX112 - ALL SIZES
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Causes burns. May cause sensitisation by skin contact.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: MODIFIED POLYAMINE 10-30%
[C] R34; [Sens.] R43; [-] R52/53

- MODIFIED HETEROCYCLIC POLYAMINE 10-30%
[Xn] R21/22; [C] R34; [Sens.] R43

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact: Corneal burns may occur. May cause permanent damage.
Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If

[cont...]

SAFETY DATA SHEET
EPOXYSET 112 - HARDENER COMPONENT

unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: Buff

Odour: Characteristic odour

SAFETY DATA SHEET
EPOXYSET 112 - HARDENER COMPONENT

Evaporation rate: Moderate
Solubility in water: Slightly soluble
Also soluble in: Most organic solvents.
Viscosity: Highly viscous
Relative density: 1.55-1.75
pH: alkaline

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: May cause sensitisation by skin contact.
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: No data available.
Bioaccumulative potential: No data available.
Other adverse effects: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2735	ADR Class: 8
Packing group: I	Classification code: C7
Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.	
Labelling: 8	Hazard ID no: 88



SAFETY DATA SHEET
EPOXYSET 112 - HARDENER COMPONENT**IMDG / IMO**

UN no: 2735 **Class:** 8
Packing group: I **EmS:** F-A,S-B
Marine pollutant: .
Labelling: 8

IATA / ICAO

UN no: 2735 **Class:** 8
Packing group: I
Packing instructions: 807(P&CA); 809(CAO)
Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R34: Causes burns.
R43: May cause sensitisation by skin contact.

Safety phrases: S1/2: Keep locked up and out of the reach of children.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Haz. ingredients (label): MODIFIED POLYAMINE; MODIFIED HETEROCYCLIC POLYAMINE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R34: Causes burns.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R21/22: Harmful in contact with skin and if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.