



SAFETY DATA SHEET
MULTI MAINTENANCE SPRAY

Page 1
Issued: 30/7/09
Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MULTI MAINTENANCE SPRAY
Product code: MULTI
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: paul@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Repeated exposure may cause skin dryness or cracking.
Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BUTANE 10-30%
EINECS: 203-448-7 CAS: 106-97-8
[F+] R12

- REFINED MINERAL OIL 1-10%
- LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),
HYDROTREATED HEAVY 50-70%
EINECS: 265-150-3 CAS: 64742-48-9
[T] R46; [Xn] R65; [-] R10; [-] R66

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be irritation of the throat.
Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET

MULTI MAINTENANCE SPRAY

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: BUTANE
WEL (8 hr TWA): 1450 mg/m³ WEL (15 min STEL): 1810 mg/m³

- REFINED MINERAL OIL
WEL (8 hr TWA): 5mg/m³ WEL (15 min STEL): 10mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol
Colour: Colourless
Odour: Aromatic
Evaporation rate: Fast
Solubility in water: Not miscible
Also soluble in: Most organic solvents.
Flash point°C: -40
Relative density: 0.777

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.
Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: REFINED MINERAL OIL
ORL RAT LD50 >2 g/kg
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS
Labelling: 2.1



SAFETY DATA SHEET
MULTI MAINTENANCE SPRAY

IMDG / IMO

UN no: 1950	Class: 2	
EmS: 2-13	Marine pollutant: .	
Labelling: 2.1		

IATA / ICAO

UN no: 1950	Class: 2	
Labelling: 2.1		

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.
S23: Do not breathe spray.
S24: Avoid contact with skin.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S46: If swallowed, seek medical advice immediately and show this container or label.
S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Haz. ingredients (label): LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R12: Extremely flammable.
R46: May cause heritable genetic damage.
R65: Harmful: may cause lung damage if swallowed.
R10: Flammable.
R66: Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET
MULTI MAINTENANCE SPRAY

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.