



SAFETY DATA SHEET
PAINT AND VARNISH STRIPPER

Page 1
Issued: 28/1/2010
Revision No: 4

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PAINT AND VARNISH STRIPPER
Product code: PAINTSTP
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: METHANOL 1-10%
EINECS: 200-659-6 CAS: 67-56-1
[F] R11; [T] R23/24/25; [T] R39/23/24/25
• DICHLOROMETHANE 70-90%
EINECS: 200-838-9 CAS: 75-09-2
[Xn] R40

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

[cont...]

SAFETY DATA SHEET
PAINT AND VARNISH STRIPPER

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: METHANOL
WEL (8 hr TWA): 266 mg/m³ WEL (15 min STEL): 333 mg/m³

- DICHLOROMETHANE
WEL (8 hr TWA): 350 mg/m³ WEL (15 min STEL): 1060 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**State:** Liquid**Colour:** White opaque liquid**Odour:** Slightly sweet solvent odour**Solubility in water:** Slightly soluble**Also soluble in:** Most organic solvents.**Boiling point/range°C:** 39**Flash point°C:** >100**Relative density:** 2.93**VOC g/l:** 1180-1220**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Hot surfaces. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes. May liberate phosgene and hydrogen chloride**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** METHANOL

IVN RAT LD50 2131 mg/kg

ORL MUS LD50 7300 mg/kg

ORL RAT LD50 5628 mg/kg

• DICHLOROMETHANE

ORL MUS LD50 4770 mg/kg

ORL RAT LD50 5350 mg/kg

SCU MUS LD50 6460 mg/kg

Chronic toxicity: Danger of serious damage to health by prolonged exposure through inhalation. Danger of serious damage to health by prolonged exposure in contact with skin. Danger of serious damage to health by prolonged exposure if swallowed.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Only slightly biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Dispose of according to local or national legislation

SAFETY DATA SHEET
PAINT AND VARNISH STRIPPER

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2810 **ADR Class:** 6.1
Packing group: III **Classification code:** T1
Shipping name: TOXIC LIQUID, ORGANIC, N.O.S.
Labelling: 6.1 **Hazard ID no:** 60

**IMDG / IMO**

UN no: 2810 **Class:** 6.1
Packing group: III **EmS:** F-A,S-A
Marine pollutant: .
Labelling: 6.1

IATA / ICAO

UN no: 2810 **Class:** 6.1
Packing group: III
Packing instructions: 611(P&CA); 618(CAO)
Labelling: 6.1

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R40: Limited evidence of a carcinogenic effect.
R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Safety phrases: S2: Keep out of the reach of children.
S36/37: Wear suitable protective clothing and gloves.
S46: If swallowed, seek medical advice immediately and show this container or label.

Haz. ingredients (label): METHANOL; DICHLOROMETHANE

SAFETY DATA SHEET
PAINT AND VARNISH STRIPPER

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R11: Highly flammable.
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.
R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40: Limited evidence of a carcinogenic effect.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.