



**SAFETY DATA SHEET**  
STICK 2 TOUCH UP ENAMEL

Page 1  
Issued: 13/11/2009  
Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** STICK 2 TOUCH UP ENAMEL  
**Company name:** EVERBUILD BUILDING PRODUCTS LTD  
SITE 41, KNOWSTHORPE WAY  
CROSS GREEN INDUSTRIAL ESTATE  
LEEDS  
WEST YORKSHIRE  
LS9OSW  
ENGLAND  
Tel: 0044 113 240 3456  
Fax: 0044 113 240 0024  
Emergency tel: 0044 113 240 3456 (office hours only)  
Email: paul@everbuild.co.uk

**2. HAZARDS IDENTIFICATION**

**Main hazards:** Flammable. Irritating to eyes and skin. May cause sensitisation by inhalation. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

- Hazardous ingredients:** 2-METHYLPROPAN-1-OL 1-10%  
EINECS: 201-148-0 CAS: 78-83-1  
[-] R10; [Xi] R37/38; [Xi] R41; [-] R67
- ACETONE 1-10%  
EINECS: 200-662-2 CAS: 67-64-1  
[F] R11; [Xi] R36; [-] R66; [-] R67
  - ISOBUTYL ACETATE 1-10%  
EINECS: 203-745-1 CAS: 110-19-0  
[F] R11; [-] R66
  - 2-BUTOXYETHANOL 1-10%  
EINECS: 203-905-0 CAS: 111-76-2  
[Xn] R20/21/22; [Xi] R36/38
  - ALKYD RESIN SOLUTION 10-30%  
[F] R11; [Xn] R20/21/22; [Xi] R36/38; [Sens.] R42
  - N-BUTYL ACETATE 10-30%  
EINECS: 204-658-1 CAS: 123-86-4  
[-] R10; [-] R66; [-] R67

**SAFETY DATA SHEET**  
STICK 2 TOUCH UP ENAMEL**4. FIRST AID MEASURES (SYMPTOMS)**

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be pain and redness.
- Ingestion:** May cause dizziness. May cause lung damage if swallowed
- Inhalation:** Headache, dizziness, nausea

**4. FIRST AID MEASURES (ACTION)**

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. For persistent irritation seek medical advice.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If symptoms persist seek medical advice.

**5. FIRE-FIGHTING MEASURES**

- Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water.
- Exposure hazards:** In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers.
- Clean-up procedures:** Allow to solidify and remove by mechanical means.

**7. HANDLING AND STORAGE**

- Handling requirements:** Ensure there is sufficient ventilation of the area.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition.
- Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Hazardous ingredients:** ACETONE  
WEL (8 hr TWA): 1210 mg/m<sup>3</sup> WEL (15 min STEL): 3620 mg/m<sup>3</sup>
- ISOBUTYL ACETATE  
WEL (8 hr TWA): 724 mg/m<sup>3</sup> WEL (15 min STEL): 903 mg/m<sup>3</sup>
  - 2-BUTOXYETHANOL  
WEL (8 hr TWA): 25 ppm WEL (15 min STEL): 50 ppm
  - N-BUTYL ACETATE  
WEL (8 hr TWA): 724 mg/m<sup>3</sup> WEL (15 min STEL): 966 mg/m<sup>3</sup>
- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Nitrile gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** White

**Odour:** Characteristic odour

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Viscosity value:** 200-250sn

**Viscosity test method:** 20°C DIN4

**Flash point°C:** 21

**Relative density:** ~1.1g/cm<sup>3</sup>

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Sources of ignition. Flames.

**Materials to avoid:** Strong acids. Strong bases.

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**Hazardous ingredients:** ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

- ISOBUTYL ACETATE

ORL RAT LD50 13400 mg/kg

ORL RBT LD50 4763 mg/kg

SKN RBT LD50 >17400 mg/kg

- 2-BUTOXYETHANOL

IVN RAT LD50 307 mg/kg

ORL MUS LD50 1230 mg/kg

ORL RAT LD50 470 mg/kg

- N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Dispose of according to local or national legislation

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 1263	<b>ADR Class:</b> 3
<b>Packing group:</b> III	<b>Classification code:</b> F1
<b>Shipping name:</b> PAINT	
<b>Labelling:</b> 3	<b>Hazard ID no:</b> 30

**IMDG / IMO**

<b>UN no:</b> 1263	<b>Class:</b> 3
<b>Packing group:</b> III	<b>EmS:</b> F-E,S-E*
<b>Marine pollutant:</b> .	
<b>Labelling:</b> 3	

**IATA / ICAO**

<b>UN no:</b> 1263	<b>Class:</b> 3
<b>Packing group:</b> III	
<b>Packing instructions:</b> 309(P&CA); 310(CAO)	
<b>Labelling:</b> 3	

**15. REGULATORY INFORMATION**

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.  
R36/38: Irritating to eyes and skin.  
R42: May cause sensitisation by inhalation.

**SAFETY DATA SHEET**  
STICK 2 TOUCH UP ENAMEL

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.

S3/7: Keep container tightly closed in a cool place.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe fumes.

S29: Do not empty into drains.

S46: If swallowed, seek medical advice immediately and show this container or label.

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

**Haz. ingredients (label):** ALKYD RESIN SOLUTION; N-BUTYL ACETATE

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Risk phrases used in s.3:** R10: Flammable.

R37/38: Irritating to respiratory system and skin.

R41: Risk of serious damage to eyes.

R67: Vapours may cause drowsiness and dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R36/38: Irritating to eyes and skin.

R42: May cause sensitisation by inhalation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.