



**SAFETY DATA SHEET**  
STICK 2 RAPID EPOXY - RESIN COMPONENT

Page 1  
Issued: 31/7/09  
Revision No: 2

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** STICK 2 RAPID EPOXY - RESIN COMPONENT  
**Company name:** EVERBUILD BUILDING PRODUCTS LTD  
SITE 41, KNOWSTHORPE WAY  
CROSS GREEN INDUSTRIAL ESTATE  
LEEDS  
WEST YORKSHIRE  
LS9OSW  
ENGLAND  
Tel: 0044 113 240 3456  
Fax: 0044 113 240 0024  
Emergency tel: 0044 113 240 3456 (office hours only)  
Email: paul@everbuild.co.uk

**2. HAZARDS IDENTIFICATION**

**Main hazards:** Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} >90%  
EINECS: 500-033-5 CAS: 25068-38-6  
[Xi] R36/38; [Sens.] R43; [N] R51/53

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat.  
**Inhalation:** Exposure may cause coughing or wheezing.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.  
**Ingestion:** Wash out mouth with water. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.  
**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

## SAFETY DATA SHEET

STICK 2 RAPID EPOXY - RESIN COMPONENT

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 7. HANDLING AND STORAGE

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties. Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** Yellow

**Odour:** Irritating odour

**Evaporation rate:** Moderate

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Viscosity value:** 135000

**Viscosity test method:** Brookfield (cps)

**Boiling point/range°C:** >150

**Flash point°C:** >150

**Relative density:** 1.16

### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**SAFETY DATA SHEET**  
STICK 2 RAPID EPOXY - RESIN COMPONENT

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

### 11. TOXICOLOGICAL INFORMATION

**Hazardous ingredients:** BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL MUS LD50 15600 mg/kg

ORL RAT LD50 11400 mg/kg

SKN RBT LD50 >20 ml/kg

**Chronic toxicity:** May cause sensitisation by skin contact.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12. ECOLOGICAL INFORMATION

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Only slightly biodegradable.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** Toxic to aquatic organisms.

### 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Dispose of according to local or national legislation

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### 14. TRANSPORT INFORMATION

#### ADR / RID

**UN no:** 3082

**ADR Class:** 9

**Packing group:** III

**Classification code:** M6

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**Labelling:** 9

**Hazard ID no:** 90



#### IMDG / IMO

**UN no:** 3082

**Class:** 9

**Packing group:** III

**EmS:** F-A,S-F

**Marine pollutant:** .

**Labelling:** 9

**SAFETY DATA SHEET**  
STICK 2 RAPID EPOXY - RESIN COMPONENT

**IATA / ICAO**

**UN no:** 3082 **Class:** 9  
**Packing group:** III  
**Packing instructions:** 914  
**Labelling:** 9

**15. REGULATORY INFORMATION**

**Hazard symbols:** Dangerous for the environment.  
Irritant.



**Risk phrases:** R36/38: Irritating to eyes and skin.  
R43: May cause sensitisation by skin contact.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.  
S24/25: Avoid contact with skin and eyes.  
S29: Do not empty into drains.  
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.  
S46: If swallowed, seek medical advice immediately and show this container or label.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Contains epoxy constituents. See information supplied by the manufacturer.

**Haz. ingredients (label):** BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.3:** R36/38: Irritating to eyes and skin.  
R43: May cause sensitisation by skin contact.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.