



SAFETY DATA SHEET
EPOXYSET 106 - HARDENER

Page 1
Issued: 20/11/2008
Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPOXYSET 106 - HARDENER
Product code: EPOX106 - ALL SIZES
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: MODIFIED CYCLOALIPHATIC AMINE >90%
[Xn] R20/21/22; [C] R34; [Sens.] R43; [-] R52/53

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact: Corneal burns may occur. May cause permanent damage.
Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. Transfer to hospital as soon as possible.

[cont...]

SAFETY DATA SHEET
EPOXYSET 106 - HARDENER

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale yellow

Odour: Acrid

Evaporation rate: Moderate
Solubility in water: Slightly soluble
Flash point°C: >100
Relative density: 1.02
pH: alkaline

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: May cause sensitisation by skin contact.
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: No data available.
Bioaccumulative potential: No data available.
Other adverse effects: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2735	ADR Class: 8
Packing group: III	Classification code: C7
Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.	
Labelling: 8	Hazard ID no: 80

**IMDG / IMO**

UN no: 2735	Class: 8
Packing group: III	EmS: F-A,S-B

Marine pollutant: .**Labelling:** 8**IATA / ICAO****UN no:** 2735**Class:** 8**Packing group:** III**Packing instructions:** 818(P&CA); 820(CAO)**Labelling:** 8**15. REGULATORY INFORMATION****Hazard symbols:** Corrosive.

Risk phrases: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R34: Causes burns.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S1/2: Keep locked up and out of the reach of children.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29: Do not empty into drains.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Haz. ingredients (label): MODIFIED CYCLOALIPHATIC AMINE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R34: Causes burns.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

SAFETY DATA SHEET
EPOXYSET 106 - HARDENER

be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.