

DECLARATION OF PERFORMANCE
DoP No. ANCHGN/CPR-1/2016

1. Unique identification code of the product-type: **Anchor Set Green**
2. Type, batch or serial number or any other element **ETA-13/0723**
allowing identification of the construction product as required **Batch number: see packaging of the product.**
pursuant to Article 11(4)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Bonded injection type anchor sizes M8, M10, M12, M16, M20, M24
For use in	For use in non-cracked concrete in the range C20/25 as a minimum up to a maximum of C50/60 according to EN 206-1:2000-12.
Option / Category	ETAG001 Part 5 Option 7
Loading	Tension, shear, combined tension and shear.
Material	<u>zinc-plated steel:</u> dry internal conditions only covered sizes: M8, M10, M12, M16, M20, M24 <u>stainless steel (marking A4):</u> internal and external use without particular aggressive conditions covered sizes: M8, M10, M12, M16, M20, M24 <u>highly corrosion resistant steel (marking C):</u> internal and external use with particular aggressive conditions covered sizes: M8, M10, M12, M16, M20, M24
Temperature range (if applicable)	Service temperature range: -40°C to +80°C. Maximum short term temperature = +80°C. Maximum long term temperature = +50°C.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Everbuild Building Products Ltd. Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS90SW

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

--

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

--

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

TZUS Praha 13/0723

on the basis of

ETAG001 Part 1 and ETAG001 Part 5

The notified body **1020** performed description of the third party tasks as set out in Annex V

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	TR029	ETA-13/0723, annex 6	ETAG 001 Part 1, 5
characteristic resistance for shear	TR029	ETA-13/0723, annex 7	
minimum spacing and minimum edge distance	TR029	ETA-13/0723, annex 5	
displacement for serviceability limit state	TR029	ETA-13/0723, annex 8	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Paul Thomas

A. Scanlon

Name 1 Paul Thomas
 Function R&D Manager
 Place and date of issue Leeds 31/03/2016

Name 2 Andrew Scanlon
 Function Chemist