



# 203 ACCELERATOR & FROSTPROOFER

## DECLARATION OF PERFORMANCE

### No. ACC/2-CPR/2018

|           |  |   |
|-----------|--|---|
| <b>1</b>  | <b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b> | ACC5L / ACCE25L   |
| <b>2</b>  | <b>INTENDED USE/S</b>                                  | Hardening and accelerating admixture  |
| <b>3</b>  | <b>MANUFACTURER:</b>                                   | Everbuild Building Products LTD<br>Site 41, Knowsthorpe Way,<br>Cross Green Industrial Estate,<br>LS9 0SW |
| <b>4</b>  | <b>AUTHORISED REPRESENTATIVE:</b>                      | Not Applicable  |
| <b>5</b>  | <b>SYSTEM/S OF AVCP:</b>                               | System 2+   |
| <b>6a</b> | <b>HARMONISED STANDARD:</b>                            | EN934-2:2009 +A1:2012   |
|           | Notified body/ies:                                     | 0086  |

**7 DECLARED PERFORMANCE/S**

| Essential Characteristics     | Performance  | AVCP | Harmonised Technical Specification |
|-------------------------------|--|------|------------------------------------|
| Chloride ion content          | <0.1% w/w  |      |                                    |
| Alkali Content                | <2% w/w  |      |                                    |
| Corrosion Behaviour           | Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate |      |                                    |
| Compressive Strength          | >120% of control 20°C and 24 hours   |      | EN934-2:2009                       |
|                               | >90% of control 20°C and 28 days   |      |                                    |
|                               | >130% of control 5°C and 48 hours  |      |                                    |
| Air Content in Fresh Concrete | ≤2% by volume above control  |      |                                    |
| Dangerous Substances          | None (see MSDS)  |      |                                    |
|                               |  |      |                                    |
|                               |  |      |                                    |


**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas  
 Function: Technical Product Co-ordinator  
 At Leeds on 19 March 2018

Name : Andrew Stockill  
 Function: QA/QC Supervisor  
 At Leeds on 19 March 2018





End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

ACC5L/ACCE25L  
 ACC/2-CPR/2018  
 2018/03 , ver. 02  
 1213





Everbuild Building Products LTD, Leeds, UK

DoP No. ACC/2-CPR/2018

EN934-2:2009 +A1:2012

Notified Body 0086

### Hardening and accelerating admixture

|                               |   |
|-------------------------------|---|
| Chloride ion content          | <0.1% w/w   |
| Alkali Content                | <2% w/w   |
| Corrosion Behaviour           | Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate                              |
| Compressive Strength          | >120% of control 20°C and 24 hours<br>>90% of control 20°C and 28 days<br>>130% of control 5°C and 48 hours |
| Air Content in Fresh Concrete | ≤2% by volume above control   |
| Dangerous Substances          | None (see MSDS)   |
|                               |   |
|                               |   |

For DoP see [www.everbuild.co.uk](http://www.everbuild.co.uk)

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

ACC5L/ACCE25L  
ACC/2-CPR/2018  
2018/03 , ver. 02  
1213



**Declaration of Performance**

ACC5L/ACCE25L  
ACC/2-CPR/2018  
2018/03 , ver. 02  
1213

