

711 Rapid Set Flexiplus

DECLARATION OF PERFORMANCE

No. 711/2-CPR/2018

| | | |
|----|--|--|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | RSPLUS |
| 2 | INTENDED USE/S | Improved fast setting deformable cementitious adhesive with reduced slip and extended open time |
| 3 | MANUFACTURER: | Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 3 |
| 6a | HARMONISED STANDARD: | BS EN12004:2007+A1:2012 |
| | Notified body/ies: | 1289 |

Declaration of Performance

711 Rapid Set Flexiplus
711/2-CPR/2018
2018/02 , ver02.
1213

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Harmonised Technical Specification |
|---|------------------------|------|------------------------------------|
| Reaction to fire | NPD | | |
| Initial Tensile Adhesive Strength 28 days | ≥1.0 N/mm ² | | |
| Initial Tensile Adhesive Strength 6 hours | ≥0.5 N/mm ² | | |
| Water Immersion Tensile Strength | ≥0.5 N/mm ² | | |
| Heat Aging Tensile Strength | ≥1.0 N/mm ² | | |
| Freeze / Thaw Tensile Strength | ≥1.0 N/mm ² | | EN12004:2007 |
| Open Time Tensile Strength after 30 minutes | ≥0.1 N/mm ² | | +A1:2012 |
| Slip | ≤0.5mm | | |
| Transverse Deformation | ≥2.5mm and <5mm | | |
| Release of Dangerous Substances | See MSDS | | |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
 Function: Technical Product Coordinator
 At Leeds on date of issue

Name : Andrew Stockill
 Function: QA/QC Supervisor
 At Leeds on date of issue

.....

End of information as required by Regulation (EU) No 305/2011



18

Everbuild Building Products LTD, Leeds, UK

DoP No. 711/2-CPR/2018

BS EN12004:2007+A1:2012

Notified Body 1289

Improved fast setting deformable cementitious adhesive with reduced slip and extended open time

| | |
|---|------------------------|
| Reaction to fire | NPD |
| Initial Tensile Adhesive Strength 28 days | ≥1.0 N/mm ² |
| Initial Tensile Adhesive Strength 6 hours | ≥0.5 N/mm ² |
| Water Immersion Tensile Strength | ≥0.5 N/mm ² |
| Heat Aging Tensile Strength | ≥1.0 N/mm ² |
| Freeze / Thaw Tensile Strength | ≥1.0 N/mm ² |
| Open Time Tensile Strength after 30 minutes | ≥0.1 N/mm ² |
| Slip | ≤0.5mm |
| Transverse Deformation | ≥2.5mm and <5mm |
| Release of Dangerous Substances | See MSDS |

<http://www.everbuild.co.uk/downloads/>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

711 Rapid Set Flexiplus
711/2-CPR/2018
2018/02 , ver02.
1213

Declaration of Performance

711 Rapid Set Flexiplus
711/2-CPR/2018
2018/02 , ver02.
1213

