



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

#### No JETCEM/1-CPR/2013

1. Identification Code	<b>Jetcem Rapid Set Cement</b>  <b>Codes: JETCEM2, JETCEM3, JETCEM6</b>
2. Type, Batch and/or Serial Number	<b>For batch number see packaging</b>
3. Intended use	<b>Concrete repair product for non- structural repair. CC Mortar (based on hydraulic cement)</b>  <b>EN1504-3 Principle 3.1</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS90SW, UK.</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 2+</b>
7. Notified Body and Tasks	<b>BSI (0086) Initial inspection and ongoing surveillance of F.P.C. system</b>  <b>Certificate of conformity reference 0086-CPD- 597711</b>
8. European technical Assessment	<b>Not applicable</b>



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

9. Declared Performance	<b>EN1504-3 (2005) ) Concrete repair product for non structural repair. CC mortar (based on hydraulic cement) Class R2</b>
Compressive Strength	<b>Class R4</b>
Chloride ion content	<b>≤ 0.05%</b>
Adhesion strength by pull off test	<b>≥ 1.5MPa</b>
Restrained shrinkage/expansion	<b>NPD</b>
Carbonation resistance	<b>NPD</b>
Elastic Modulus	<b>≥ 15GPa</b>
Thermal Compatibility: Part 4 Dry Cycling	<b>≥ 0.8MPa</b>
Skid resistance	<b>NPD</b>
Coefficient of thermal expansion	<b>NPD</b>
Capillary Adsorption	<b>≤0.5kg/m<sup>2</sup>h<sup>0.5</sup></b>
Dangerous substances	<b>Complies with 5.4</b>
Reaction to Fire	<b>Class A1</b>

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/201