

PRODUCT DATA SHEET

EVERBUILD STICK2[®] Epoxy Putty Aqua

TWO COMPONENT UNDERWATER REPAIR ADHESIVE

PRODUCT DESCRIPTION

Epoxy Putty Aqua is a two component putty that has been specially formulated for permanent repairs to damp, wet areas and underwater substrates such as tanks, drums, pipes and castings.

USES

It can be applied underwater, both fresh and salt, and will bond to substrates such as fibreglass, metal, wood, concrete, ceramic, glass etc.

CHARACTERISTICS / ADVANTAGES

- Mixes in one minute.
- Totally waterproof once dried.
- Can be used on wet surfaces and underwater.

PRODUCT INFORMATION

Packaging	50g Tube
Shelf Life	36 months
Storage Conditions	Store in cool dry conditions between 0 and 20°C. Storage outside these parameters will dramatically reduce shelf life.

APPLICATION INFORMATION

Open Time	Working time from mixing – 5 minutes @ 20°C
Curing Time	60 minutes @ 20°C

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Smooth surfaces should be abraded. Wearing gloves break off the required amount of EPOXY PUTTY AQUA and mix by hand to a uniform colour. Apply to required areas immediately. Fill all voids and holes, apply pressure on damp, wet or slowly leaking surfaces. For a smooth appearance, handrub with water or a damp cloth prior to hardening. Allow to fully cure before sanding or machining.

- Will not stick polyethylene, polypropylene, or PTFE
- Do not use on bitumen, asphalt.
- Do not use as a mirror adhesive as the product may attack the mirror backing.
- Do not use below 5°C.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

LIMITATIONS

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

See safety data sheet

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDSTICK2EpoxyPuttyAqua-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet
EVERBUILD STICK2® Epoxy Putty Aqua
March 2018, Version 01.01
020204030010000193