

## PRODUCT DATA SHEET

EVERBUILD STICK2<sup>®</sup> Superglue HV

A HIGH VISCOSITY SUPERGLUE FOR POROUS AND NON POROUS SUBSTRATES.

**PRODUCT DESCRIPTION**

EVERBUILD STICK2<sup>®</sup> Superglue HV is a high viscosity industrial adhesive based on advanced cyanoacrylate technology. This formula is suitable for use on both porous and non porous substrates where a slightly delayed set is required.

**USES**

Ideal for use on:

- MDF
- Rubber
- Metals
- PVCu
- Plastics

**CHARACTERISTICS / ADVANTAGES**

- Fast setting formulation, bonds to most porous and non porous surfaces in seconds.
- Fills gaps up to 0.25mm
- Single component adhesive
- 100% solvent free
- Economical in use

<b>Solids</b>	100% Active
<b>Refractive Index</b>	1.45 (cured adhesive)
<b>Softening Point</b>	160°C

**PRODUCT INFORMATION**

<b>Chemical Base</b>	Ethyl Cyanoacrylate.
<b>Packaging</b>	Available in 20g and 50g bottles, packed in self merchandising display boxes.
<b>Colour</b>	Clear liquid.
<b>Shelf Life</b>	12 months from date of manufacture when stored as directed.
<b>Storage Conditions</b>	Store in cool, dry conditions between +5 and +25°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life.
<b>Density</b>	1.1 g/cm <sup>3</sup>
<b>Viscosity</b>	120-180 poise.

**TECHNICAL INFORMATION**

<b>Shear Strength</b>	>20Nmm <sup>2</sup> (steel-steel ASTM D1002)
<b>Service Temperature</b>	-60 to +80°C

## APPLICATION INFORMATION

---

### Curing Time

Setting time range:

- 15-40 seconds plastic to plastic
  - 10-15 seconds rubber to rubber
  - 10-60 seconds degreased metal to metal
- 

## APPLICATION INSTRUCTIONS

### APPLICATION METHOD / TOOLS

The surfaces to be glued should be clean, dry and free from dust, grease and other contaminants. Materials should be stored in a warm environment prior to bonding to avoid chilling of the glue line, which leads to extended setting times. Where possible, ensure working environment has a relative humidity of 50+%. Apply adhesive to one surface only. Press surfaces together and hold for 10 seconds or as indicated below. Cure speed is rapid so exercise care when aligning.

from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### LIMITATIONS

- Ensure surfaces are degreased prior to bonding.
- Ensure surfaces are close fitting. This adhesive will not bridge gaps.
- Do not use in applications involving constant water immersion.
- Do not use on bitumen or tar leaching products. As the manufacturer cannot know all the uses its products may be put to, contact technical services for advice if in any doubt.

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

### ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either

**EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

**SIKA LIMITED**

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

**SIKA IRELAND LIMITED**

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

EVERBUILDSTICK2SuperglueHV-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet  
EVERBUILD STICK2® Superglue HV  
March 2018, Version 01.01  
020204030040000008