

PRODUCT DATA SHEET

EVERBUILD STICK2[®] Superglue Gel

HIGH VISCOSITY, NON-DRIP SUPERGLUE GEL

PRODUCT DESCRIPTION

EVERBUILD STICK2[®] Superglue Gel is a thixotropic ethyl cyanoacrylate based adhesive for bonding most common materials. The high viscosity formula is ideal for non drip, vertical, porous or small gap filling applications.

USES

Bonds most types of wood, plastics, metals, paper, porcelain, rubber, cardboard and leather.

CHARACTERISTICS / ADVANTAGES

- High strength.
- Sticks plastic, wood, glass, rubber, metals, ceramics, and much more.
- Re-sealable cap.
- 1 minute bond.

PRODUCT INFORMATION

Packaging	3g Tube
Colour	Clear
Shelf Life	3 years from date of manufacture in original unopened tubes.
Storage Conditions	Store in cool dry conditions between 0°C and 20°C. Storage outside these parameters will dramatically reduce shelf life.
Density	1.05 g/cm ³
Viscosity	>20 cP
Consistency	Gel

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Ensure parts to be bonded are clean and dry. Apply adhesive sparingly to one surface (take care not to apply too much adhesive). Assemble by firmly pressing parts together for 1 minute. After use clean nozzle with dry cloth or paper roll and firmly screw the cap back on the tube.

NOTE: Once surfaces are brought together an almost instant initial bond is formed. Care must be taken to

align items as contact is made.
To de-bond use Everbuild Superglue Remover.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDSTICK2SuperglueGel-en-GBEVER-(04-2018)-1-1.pdf

Product Data Sheet
EVERBUILD STICK2® Superglue Gel
April 2018, Version 01.01
020204030040000005