

# PRODUCT DATA SHEET

## Sika® MultiSeal

### BITUMINOUS SEALING TAPE

#### PRODUCT DESCRIPTION

Sika® MultiSeal is a self-adhesive, rubber modified bituminous sealing tape laminated with an aluminium foil on the upper side.

#### USES

Sika® MultiSeal is designed for sealing and repairing applications against water ingress on roofs and any other building element.

#### CHARACTERISTICS / ADVANTAGES

- Very easy to apply
- Good adhesion to many substrates
- Self-adhering
- Compatible with bituminous substrates
- Can be overpainted
- Can be applied at low temperatures

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Rubber modified, bituminous tape		
<b>Packaging</b>	<b>Length per roll (m)</b>	<b>Tape width (mm)</b>	
	10	100	
	10	150	
	10	225	
	10	300	
<b>Appearance / Colour</b>	Matt grey		
<b>Shelf Life</b>	Sika® MultiSeal has a shelf life of 24 months from the date of production, if it is stored properly in undamaged, original, sealed packaging, and if the storage conditions are met.		
<b>Storage Conditions</b>	Sika® MultiSeal shall be stored in dry conditions, protected from direct sunlight and at temperatures between +5 °C and +25 °C.		
<b>Thickness</b>	~1.2 mm		

#### TECHNICAL INFORMATION

<b>Tensile Strength</b>	~3.6 N/mm <sup>2</sup>	
<b>Elongation at Break</b>	~50 %	
<b>Reaction to Fire</b>	B2	(DIN 4102)
<b>Service Temperature</b>	-20 °C min. / +70 °C max.	

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	+5 °C min. / +40 °C max.
<b>Substrate Temperature</b>	+5 °C min. / +40 °C max., min. 3 °C above dew point temperature At temperatures below +10 °C the tape and the substrate must be warmed with a hot air fan before and during the application.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The substrate must be clean, dry, sound and homogeneous, free from oils, grease, dust and loose or friable particles.

### APPLICATION METHOD / TOOLS

Cut the tape to the required length, remove the release film and press the tape firmly onto the substrate with a suitable roller.

Overlaps must be minimum 5 cm.

Adhesion performance can be improved by heating Sika® MultiSeal tape during application.

### CLEANING OF TOOLS

Clean all tools and application equipment immediately after use with Sika® Remover-208. Once cured, residual material can only be removed mechanically. For cleaning skin use Everbuild Wonder Wipes.

## LIMITATIONS

- The upper side of Sika® MultiSeal can be over-painted with most conventional paint systems.
- Do not use Sika® MultiSeal on natural stone.
- Do not use Sika® MultiSeal for joints under water pressure or for permanent water immersion.
- Direct contact with joint sealants and adhesives must be avoided or compatibility must be tested prior to application.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

**SIKA LIMITED**

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

**SIKA IRELAND LIMITED**

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

SikaMultiSeal-en-GBEVER-(03-2018)-2-2.pdf

Product Data Sheet  
Sika® MultiSeal  
March 2018, Version 02.02  
020516050000000009