



EN 15651-1:2012

13

1213

DECLARATION OF PERFORMANCE

Sikaflex[®] EBT+

02	05	13	01	000	0	000024	1033,1009
----	----	----	----	-----	---	--------	-----------

1. Product Type: Unique identification code of the product-type:	Sikaflex[®]
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	EBT+ (Batch No. - see packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Sealant for façade for interior and exterior application (intended for use in cold climates)
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikaflex[®] EBT+ Everbuild – A Sika Company Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds LS9 0SW United Kingdom
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3 for the type testing System 3 for the reaction to fire testing
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Notified body SKZ Tecona GmbH, certification body No. 1213 performed the type testing and the testing to reaction to fire and issued test report and classification: 94931/11-VI-M1-E and 94931/11-I-M3-E

Declaration of Performance





BUILDING TRUST



Declaration of Performance

8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant

9. Declared performance

According to EN 15651-1:2012

Conditioning: Method B
 Substrate: Mortar M1, Sika® Primer-3N

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to Fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012: 4.5	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	EN ISO 7390	
Loss of Volume	≤ 10%	EN ISO 10563	
Tensile properties at maintained extension after water immersion (elastic)	NF	EN ISO 10590	
Tensile properties for non-structural sealants used in joints in cold climat areas (-30°C)	NF	EN ISO 8340 modified	
Durability	Pass	EN ISO 8340 EN ISO 9047 EN ISO 10590	

Everbuild – A Sika Company
 Site 41, Knowsthorpe Way
 Cross Green Ind Est
 Leeds, LS9 0SW
 United Kingdom

Phone: +44 113 240 3456
 Email: techservices@everbuild.co.uk
www.everbuild.co.uk
 email: sales@everbuild.co.uk



Certificate No. FM56743



FM 12504



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Paul Thomas
R&D Manager



Andrew Scanlon
Technical Manager

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For Further Information
Everbuild – A Sika Company
Site 41, Knowsthorpe Way
Cross Green Ind Est
Leeds, LS9 0SW
United Kingdom

Phone: +44 113 240 3456
Email: techservices@everbuild.co.uk
www.everbuild.co.uk