



## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: SKFLEXEBTCR /2-CPR/ 2014**

Substrate: Anodized Aluminium

Primer: No primer used

1. Identification Code	<b>SIKAFLEX EBT+ CLEAR</b>  Codes: SKFLEXEBTCR
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>
7. Notified Body and Tasks	<b>SKZ Notified Body No. 1213</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>TO EN15651-1 (2012)</b>



Type	F EXT-INT-CC
Classification	F20LM
Reaction to Fire	Class E
Loss of Volume ISO10563	≤10%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties (-30°C)	NF
Durability	Pass

Substrate: Anodized Aluminium

Primer: No primer used

1. Identification Code	<b>SIKAFLEX EBT+ CLEAR</b>  Codes: SKFLEXEBTCR
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>
7. Notified Body and Tasks	<b>SKZ Notified Body No. 1213</b>
8. European Technical Assessment	<b>Not Applicable</b>



9. Declared Performance		TO EN15651-3 (2012)
Type	<b>S</b>	
Classification	<b>XS2</b>	
Reaction to Fire	<b>Class E</b>	
Loss of Volume ISO10563	<b>≤20%</b>	
Resistance to flow ISO7390	<b>≤3 mm</b>	
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	<b>NF</b>	
Action of the microorganisms : Intensity of growth ISO 846, method B	<b>1</b>	
Durability	<b>Pass</b>	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 23/6/14