

PRODUCT DATA SHEET

EVERBUILD AFTER TILE® Grout Reviver

RESTORES TIRED GROUT BACK TO ITS ORIGINAL COLOUR

PRODUCT DESCRIPTION

EVERBUILD AFTER TILE® Grout Reviver is a high quality grout reviver formulated to restore tired grout to its original colour.

EVERBUILD AFTER TILE® Grout Reviver is manufactured with Mould Shield® the leading name in anti-bacterial solutions, providing protection in the grout against the growth of mould, mildew and bacteria in kitchens, bathrooms and other areas of high humidity.

USES

EVERBUILD AFTER TILE® Grout Reviver can be used in most ceramic wall tile applications and is particularly suitable for use in areas of high humidity such as:

- Showers
- Bathrooms
- Wetrooms
- Kitchens

CHARACTERISTICS / ADVANTAGES

- Excellent water resistance.
- Contains Mould Shield®
- Ready mixed formula - no mixing, no mess. Apply straight from the tube.

PRODUCT INFORMATION

| | |
|--------------------|--|
| Packaging | 200ml squeeze tube with sponge applicator |
| Colour | White |
| Shelf Life | 12 months from date of manufacture in original unopened container. |
| Storage Conditions | Store in cool (5 - 25°C) dry conditions. Protect from frost. |
| Density | ca. 1.46 g/cm ³ |
| pH-Value | 8.3 - 9.3 |

APPLICATION INFORMATION

| | |
|-------------|--|
| Consumption | Approximately 20m ² of tiles per 200ml pack; depending on size of tile. |
|-------------|--|

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Surfaces must be clean, dry and dust free. Remove any old mould with Everbuild Fungicidal Wash prior to application and allow to dry. Replace any damaged, loose or cracked grouting by raking and re-grouting with Forever White Powder Wall Tile Grout; then allowing to dry. Certain tiles (e.g. non glazed; metallic; textured or hand painted) may not be compatible with this product. Always test a small inconspicuous area for compatibility prior to full scale application.

APPLICATION

Remove cap and squeeze the EVERBUILD AFTER TILE® Grout Reviver tube until product is expelled. Continue squeezing and apply to grout lines in a zig zag motion ensuring even coverage and working well into existing grout. Allow to dry for 3-4 hours then remove any excess product from tiles with a damp cloth or sponge. Any residue still remaining on tiles can easily be removed by moistening; leaving for 15 minutes then removing as above.

A second application may be necessary for badly stained areas; after first coat is dry (3-4 hours). After removal of residues; polish tiles with a clean dry cloth. Allow to dry for 3-4 hours before removing from tiles with a damp cloth.

Avoid wetting tiles for 24 hours after application (longer in cold poorly ventilated/humid conditions).

CLEANING OF TOOLS

Rinse applicator sponge in warm water after use and replace cap to enable product to be used again. Wash hands with warm water and soap after use.

LIMITATIONS

- Allow to fully dry before exposing to water
- Do not use on epoxy grout
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services department for advice. In all circumstances, the manufacturer's liability is limited to the value of the manufacturer's product purchased

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDAFTERTILEGroutReviver-en-GBEVER-(04-2018)-1-1.pdf