

AQUASEAL WRS WATERPROOF TANKING TAPE/DRAIN MAT



| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|-----------|---------|
| - | AQWRSTAPE10 | 10mtr | 8 |
| - | AQWRSDRAIN | | 25 |

Product Description

Aquaseal Waterproof Tanking Tape/Drain Mat is a self-adhesive butyl backed fleece tape/mat designed to provide a waterproof seal prior to tiling on board joints, corner joints and pipe entries in shower areas, wet rooms, wet zones and anywhere where a watertight seal to a corner, gap or crack is required.

Can be tiled straight onto areas that are waterproof (i.e. wet room boards) or used prior to applying Aquaseal Tanking Membrane as part of the Aquaseal Wet Room System to promote a 100% waterproof membrane to conventional plaster and timber based boards.

The unique butyl fleece provides cross directional stability to accommodate board movements occurring in different directions at the same time, essential to provide a permanent watertight seal.

Benefits

- Self-Adhesive
- Waterproof
- Permanently flexible butyl backed fleece with cross directional stability
- Easy to apply with pre-cut release liner
- Available as a larger size square Drain Mat for standalone showers.

Areas for Use

- For showers, wet rooms and wet zones in bathrooms
- For waterproofing before tiling
- Use on all board joints, corners & pipe entries
- Can be tiled directly or over coated with Aquaseal Tanking Membrane for full wet zones

Limitations

- Do not use on timber or boards treated with spirit or stearate based coatings
- Do not use in areas subject to high temperatures
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for advice.

Surface Preparation

All surfaces must be clean sound and dust free.

Application

On timber and plaster based boards and porous substrates prime using Aquaseal Tanking Primer (where this is not available use a suitable SBR Bonding Agent, such as Everbuild 503 SBR Bond, diluted

with 4 parts water) and allow to dry before applying. Remove the release liner progressively as the tape is applied, smoothing down with a small roller (a radiator paint roller is ideal). Take care to avoid rucks in the tape.

The liner is pre-cut along the length to allow one side of a corner to be applied and smoothed prior to repeating the process on the other side of the corner. Ensure the tape is pressed carefully into the corner before sticking the other side down to avoid stress on the tape in the corners. When joining the tape, and on internal corners, ensure the tape is overlapped by at least 50mm onto the next piece.

For sealing around drains and outlets use the self-adhesive Aquaseal Waterproof Drain Mat.

The tape can be over coated with Aquaseal Waterproof Tanking Membrane immediately after application. On internal corners ensure the tape overlaps on both sides to avoid a weak spot in the centre of the internal corner.

Specific Data

| | |
|-------------------------|--------------------------|
| Appearance | Fleece Backed Butyl Tape |
| Application Temp | +5°C to +40°C |
| Service Temp | -30°C to +80°C |
| Colour | Grey |
| Solids Content | >90% |
| Coverage | 10 Linear Metres |

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in a well-ventilated room and at a maximum temperature of 30°C. Storage outside these parameters will dramatically reduce shelf life. Protect from frost.

Shelf Life

12 months from date of manufacture when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.