



DECLARATION OF PERFORMANCE

SikaSeal®-140 Multi Purpose Silicone

SKSEAL140/1-CPR/2017

1. Product Type: Unique identification code of the product-type:	SikaSeal®-140 Multi Purpose Silicone
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	See packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Sealant for facade for interior and exterior application EN 15651-1:2012, F EXT-INT
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	SikaSeal®-140 Multi Purpose Silicone Everbuild Building Products Limited – A Sika Company Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds LS9 0SW United Kingdom
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	EN 15651 System 3 for the type testing System 3 for the reaction to fire testing
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	The notified body SKZ Tecona GmbH, identification number 1213, performed the type testing and issued classification report. The notified body Exova Warrington Fire, identification number 1121, performed the testing of the reaction to fire and issued test report.
8. Notified body (ETA): In case of the	Not relevant

For further Information
Everbuild Building products
Limited – A Sika Company

Site 41, Knowsthorpe Way,
Cross Green Ind. Estate
LS9 0SW, Leeds
UK

Tel: 0113 240 3456
www.everbuild.co.uk

Distribution
 Declaration of Performance
 Identification No. **SKSEAL140**
 Edition **10.2017**
 Version No. **V1**

declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

9. Declaration of Performance

9.1 According to EN 15651-1:2012

Conditioning: Method A
 Substrate: Anodised Aluminium and Glass

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012; 4.5	
Water tightness and air tightness			
• Resistance to flow	≤ 3 mm	EN ISO 7390	
• Loss of volume	≤ 45 %	EN ISO 10563	
Adhesion/cohesion properties at maintained extension after water immersion at 23 °C	NF	EN ISO 10590	
Durability	pass	EN ISO 8339 EN ISO 9047 EN ISO 10590	



For further Information
 Everbuild Building products
 Limited – A Sika Company

Site 41, Knowsthorpe Way,
 Cross Green Ind. Estate
 LS9 0SW, Leeds
 UK

Tel: 0113 240 3456
 www.everbuild.co.uk



DECLARATION OF PERFORMANCE

SikaSeal®-140 Multi Purpose Silicone

SKSEAL140/1-CPR/2017

1. Product Type: Unique identification code of the product-type:	SikaSeal®-140 Multi Purpose Silicone
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	See packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Sealant for facade for interior and exterior application EN 15651-3:2012, S
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	SikaSeal®-140 Multi Purpose Silicone Everbuild Building Products Limited – A Sika Company Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds LS9 0SW United Kingdom
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	EN 15651 System 3 for the type testing System 3 for the reaction to fire testing
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	The notified body Ginger CEBTP, identification number 0074, performed the type testing and issued classification report. The notified body Exova Warrington Fire, identification number 1121, performed the testing of the reaction to fire and issued test report.
8. Notified body (ETA): In case of the	Not relevant

For further Information
Everbuild Building products
Limited – A Sika Company

Site 41, Knowsthorpe Way,
Cross Green Ind. Estate
LS9 0SW, Leeds
UK

Tel: 0113 240 3456
www.everbuild.co.uk

Distribution
 Declaration of Performance
 Identification No. SKSEAL140
 Edition 10.2017
 Version No. V1

declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	
---	--

9. Declaration of Performance

9.1 According to EN 15651-3:2012

Conditioning: Method A
 Substrate: Anodised Aluminium and Glass

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012; 4.5	
Water tightness and air tightness			
• Resistance to flow	≤ 3 mm	EN ISO 7390	
• Loss of volume	≤ 45 %	EN ISO 10563	
Tensile properties after water immersion at 23 °C	≥25%	EN ISO 10591	
Durability	pass	EN ISO 10591	
Action of the microorganisms : Intensity of growth method B	1	EN ISO 846	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Paul Thomas
 Technical Product
 Co-ordinator

Irena Rakstelyte
 Product Manager
 Sika Distribution

Leeds, 10/8/17



For further Information
 Everbuild Building products
 Limited – A Sika Company

Site 41, Knowsthorpe Way,
 Cross Green Ind. Estate
 LS9 0SW, Leeds
 UK

Tel: 0113 240 3456
 www.everbuild.co.uk

Distribution
 Declaration of Performance
 Identification No. SKSEAL140
 Edition 10.2017
 Version No. V1

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.



1213

1213

17

SKSEAL140/1-CPR/2017

EN 15651-1:2012

Sealant for facade for interior and exterior application
 F EXT-INT

Conditioning: Method A
 Substrate: Anodised Aluminium and Glass

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012; 4.5	
Water tightness and air tightness			
• Resistance to flow	≤ 3 mm	EN ISO 7390	
• Loss of volume	≤ 45 %	EN ISO 10563	
Adhesion/cohesion properties at maintained extension after water immersion at 23 °C	NF	EN ISO 10590	
Durability	pass	EN ISO 8339 EN ISO 9047 EN ISO 10590	



For further Information
 Everbuild Building products
 Limited – A Sika Company

Site 41, Knowsthorpe Way,
 Cross Green Ind. Estate
 LS9 0SW, Leeds
 UK

Tel: 0113 240 3456
www.everbuild.co.uk

Distribution
Declaration of Performance
Identification No.
Edition
Version No.

SKSEAL140
10.2017
V1



0074

1213

17

SKSEAL140/1-CPR/2017

EN 15651-3:2012

Non-structural sealants for sanitary joints
S

Conditioning: Method A
Substrate: Anodised Aluminium and Glass

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012; 4.5	
Water tightness and air tightness			
• Resistance to flow	≤ 3 mm	EN ISO 7390	
• Loss of volume	≤ 45 %	EN ISO 10563	
Tensile properties after water immersion at 23 °C	≥25%	EN ISO 10591	
Durability	pass	EN ISO 10591	
Action of the microorganisms : Intensity of growth method B	1	EN ISO 846	

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For further Information
Everbuild Building products
Limited – A Sika Company

Site 41, Knowsthorpe Way,
Cross Green Ind. Estate
LS9 0SW, Leeds
UK

Tel: 0113 240 3456
www.everbuild.co.uk